

flexy ECO IP



RANGE	QBO FLEXY ECO
REF.	05075-
TYPE	LEDSTRIP
DIMENSIONS	13 x 5000 mm
CUT UNIT	125 mm
MINIMUM BENDING DIAMETRE	50 mm
MAXIMUM RUN LENGTH	10000 mm
MAXIMUM CABLE LENGTH (FOR MAX RUN LENGTH)	(ø 0,5 mm) 5000 mm
GAP BETWEEN LEDs	16 mm
WEIGHT	0,500 Kg
VOLTAGE	24 V
DIMMABLE	YES
POWER	7,56 W
SERVICE LIFE	> 50000 HRS
IP RATING	IP68
LIGHTING DISTRIBUTION	DIRECT / INDIRECT
CRI	80
MACADAM ELLIPSE	5
LPM	48 lpm
OPENING DEGREES	120 °
WARRANTY	3 YEARS

*DOES NOT NEED DISSIPATION

COLOR TEMPERATURE (K)	LIGHTING FLUX (lm)	LUMINOUS EFFICACY (lm/W)
2200	520	68,8
2700	532	70,4
3000	540	71,4
4000	580	76,7
6500	575	76,1



CODE	DESCRIPTION
050752258068	LEDSTRIP FLEXY Eco 7,56W/m 2200K 5m Ra80 520lm/m 48leds/m IP68 24V
050752758068	LEDSTRIP FLEXY Eco 7,56W/m 2700K 5m Ra80 532lm/m 48leds/m IP68 24V
050753058068	LEDSTRIP FLEXY Eco 7,56W/m 3000K 5m Ra80 540lm/m 48leds/m IP68 24V
050754058068	LEDSTRIP FLEXY Eco 7,56W/m 4000K 5m Ra80 580lm/m 48leds/m IP68 24V
050756558068	LEDSTRIP FLEXY Eco 7,56W/m 6500K 5m Ra80 575lm/m 48leds/m IP68 24V

