




LT Surface



RANGE	LT
REF.	LTLED-
TYPE	LED PROJECTOR
DIMENSIONS	100 x 57 mm
FREE HEIGHT FOR INSTALLATION	30 mm
WEIGHT	0,189 Kg
MATERIAL	ALUMINUM
FINISH	BRASS/WHITE/BLACK
VOLTAGE	220 - 240 V
FREQUENCY	50 / 60 Hz
FEEDER KIT	350 mA (INCLUDED)
DIMMABLE	YES
POWER	8,8 W
POWER FACTOR	0,90
SERVICE LIFE	60.000 h
CUT DIAMETER	MAX Ø 30 mm
IP RATING	IP44
LIGHTING DISTRIBUTION	DIRECT
COLOR TEMPERATURE	3000 K
CRI	90
MACADAM ELLIPSE	3
LIGHTING FLUX	1035 lm
LUMINOUS EFFICACY	118 lm/W
OPENING DEGREES	10° /24° /36°
TILTING VERTICAL AXIS	90°
ROTATION HORIZONTAL AXIS	350°



CODE	DESCRIPTION
LTLED883090104400	LT LED surface 8,8W 3000K 10° Ra90 IP44 1035lm white
LTLED883090244400	LT LED surface 8,8W 3000K 24° Ra90 IP44 1035lm white
LTLED883090364400	LT LED surface 8,8W 3000K 36° Ra90 IP44 1035lm white
LTLED883090104402	LT LED surface 8,8W 3000K 10° Ra90 IP44 1035lm brass
LTLED883090244402	LT LED surface 8,8W 3000K 24° Ra90 IP44 1035lm brass
LTLED883090364402	LT LED surface 8,8W 3000K 36° Ra90 IP44 1035lm brass
LTLED883090104409	LT LED surface 8,8W 3000K 10° Ra90 IP44 1035lm black
LTLED883090244409	LT LED surface 8,8W 3000K 24° Ra90 IP44 1035lm black
LTLED883090364409	LT LED surface 8,8W 3000K 36° Ra90 IP44 1035lm black