

21x21 luminaire^{recessed}



| | |
|-----------------------|--------------------------|
| RANGE | PROFILE 21X21 LUMINAIRE |
| REF. | QBOP21X21E- |
| TYPE | RECESSED MOUNTING |
| DIMENSIONS | 21x 21x 1200 mm |
| MATERIAL | ALUMINUM |
| FINISH | WHITE / ALUMINUM / BLACK |
| VOLTAGE | 220 - 240 V |
| FREQUENCY | 50 / 60 Hz |
| FEEDER KIT | INCLUDED |
| DIMMABLE | YES |
| POWER | 23,1 W |
| POWER FACTOR | 0,95 |
| SERVICE LIFE | 30.000 h |
| INSULATION CLASS | CLASS II |
| IP RATING | IP20 |
| LIGHTING DISTRIBUTION | DIRECT |
| COLOR TEMPERATURE | 2700 / 3000 / 4000 K |
| CRI | 80 |
| LIGHTING FLUX | 2285 / 2345 / 2465 lm |
| LUMINOUS EFFICACY | 99 / 101,6 / 106,8 lm/W |



| CODE | DESCRIPTION |
|-----------------------|---|
| QBOP21X21E2780D120000 | PROFILE 21X21 recessed 23,1 W 2700K Ra80 2285lm IP20 dali 1200mm white |
| QBOP21X21E3080D120000 | PROFILE 21X21 recessed 23,1 W 3000K Ra80 2345lm IP20 dali 1200mm white |
| QBOP21X21E4080D120000 | PROFILE 21X21 recessed 23,1 W 4000K Ra80 2465lm IP20 dali 1200mm white |
| QBOP21X21E2780D120001 | PROFILE 21X21 recessed 23,1 W 2700K Ra80 2285lm IP20 dali 1200mm aluminum |
| QBOP21X21E3080D120001 | PROFILE 21X21 recessed 23,1 W 3000K Ra80 2345lm IP20 dali 1200mm aluminum |
| QBOP21X21E4080D120001 | PROFILE 21X21 recessed 23,1 W 4000K Ra80 2465lm IP20 dali 1200mm aluminum |
| QBOP21X21E2780D120009 | PROFILE 21X21 recessed 23,1 W 2700K Ra80 2285lm IP20 dali 1200mm black |
| QBOP21X21E3080D120009 | PROFILE 21X21 recessed 23,1 W 3000K Ra80 2345lm IP20 dali 1200mm black |
| QBOP21X21E4080D120009 | PROFILE 21X21 recessed 23,1 W 4000K Ra80 2465lm IP20 dali 1200mm black |

