



## 21x21 luminaire<sup>circular</sup>

RANGE	PROFILE 21X21 LUMINAIRE
REF.	QBOP21X21SC-
TYPE	SURFACE MOUNTING
DIMENSIONS	21x21xØ1000 mm
MATERIAL	ALUMINUM
FINISH	WHITE / ALUMINUM / BLACK
VOLTAGE	100 - 277 V
FREQUENCY	50 / 60 Hz
FEEDER KIT	INCLUDED
DIMMABLE	NO
POWER	60,3 W
POWER FACTOR	0,95
SERVICE LIFE	30.000 h
INSULATION CLASS	CLASS II
IP RATING	IP20
LIGHTING DISTRIBUTION	DIRECT
COLOR TEMPERATURE	2700 / 3000 / 4000 K
CRI	80
LIGHTING FLUX	5965 / 6125 / 6440 lm
LUMINOUS EFFICACY	99 / 101,6 / 106,8 lm/W



CODE	DESCRIPTION
QBOP21X21SC2780100000	PROFILE 21X21 circular surface 60,3W 2700K Ra80 5965lm IP20 1000mm white
QBOP21X21SC3080100000	PROFILE 21X21 circular surface 60,3W 3000K Ra80 6125lm IP20 1000mm white
QBOP21X21SC4080100000	PROFILE 21X21 circular surface 60,3W 4000K Ra80 6440lm IP20 1000mm white
QBOP21X21SC2780100001	PROFILE 21X21 circular surface 60,3W 2700K Ra80 5965lm IP20 1000mm aluminum
QBOP21X21SC3080100001	PROFILE 21X21 circular surface 60,3W 3000K Ra80 6125lm IP20 1000mm aluminum
QBOP21X21SC4080100001	PROFILE 21X21 circular surface 60,3W 4000K Ra80 6440lm IP20 1000mm aluminum
QBOP21X21SC2780100009	PROFILE 21X21 circular surface 60,3W 2700K Ra80 5965lm IP20 1000mm black
QBOP21X21SC3080100009	PROFILE 21X21 circular surface 60,3W 3000K Ra80 6125lm IP20 1000mm black
QBOP21X21SC4080100009	PROFILE 21X21 circular surface 60,3W 4000K Ra80 6440lm IP20 1000mm black

