

21x21 luminaire^{circular}



RANGE	PROFILE 21X21LUMINAIRE
REF.	QBOP21X21SC-
TYPE	SUSPENDED MOUNTING
DIMENSIONS	21x21xØ1000 mm
MATERIAL	ALUMINUM
FINISH	WHITE / ALUMINUM / BLACK
VOLTAGE	220 - 240 V
FREQUENCY	50 / 60 Hz
FEEDER KIT	INCLUDED
DIMMABLE	YES
POWER	60,3 W
POWER FACTOR	0,95
SERVICE LIFE	30.000 h
INSULATION CLASS	CLASS II
IP RATING	IP20
LIGHTING DISTRIBUTION	DIRECT
COLOR TEMPERATURE	2700 / 3000 / 4000 K
CRI	80
LIGHTING FLUX	5965 / 6125 / 6440 lm
LUMINOUS EFFICACY	99 / 101,6 / 106,8 lm/W



CODE	DESCRIPTION
QBOP21X21SCY2780D100000	PROFILE 21X21 circular suspended 60,3W 2700K Ra80 5965lm IP20 dali 1000mm white
QBOP21X21SCY3080D100000	PROFILE 21X21 circular suspended 60,3W 3000K Ra80 6125lm IP20 dali 1000mm white
QBOP21X21SCY4080D100000	PROFILE 21X21 circular suspended 60,3W 4000K Ra80 6440lm IP20 dali 1000mm white
QBOP21X21SCY2780D100001	PROFILE 21X21 circular suspended 60,3W 2700K Ra80 5965lm IP20 dali 1000mm aluminum
QBOP21X21SCY3080D100001	PROFILE 21X21 circular suspended 60,3W 3000K Ra80 6125lm IP20 dali 1000mm aluminum
QBOP21X21SCY4080D100001	PROFILE 21X21 circular suspended 60,3W 4000K Ra80 6440lm IP20 dali 1000mm aluminum
QBOP21X21SCY2780D100009	PROFILE 21X21 circular suspended 60,3W 2700K Ra80 5965lm IP20 dali 1000mm black
QBOP21X21SCY3080D100009	PROFILE 21X21 circular suspended 60,3W 3000K Ra80 6125lm IP20 dali 1000mm black
QBOP21X21SCY4080D100009	PROFILE 21X21 circular suspended 60,3W 4000K Ra80 6440lm IP20 dali 1000mm black

