


## 21x21 luminaire suspended



RANGE	PROFILE 21X21 LUMINAIRE
REF.	QBOP21X21SY-
TYPE	SUSPENDED MOUNTING
DIMENSIONS	21x 21x 1500 mm
MATERIAL	ALUMINUM
FINISH	WHITE / ALUMINUM / BLACK
VOLTAGE	100 - 277 V
FREQUENCY	50 / 60 Hz
FEEDER KIT	INCLUDED
DIMMABLE	NO
POWER	28,8 W
POWER FACTOR	0,95
SERVICE LIFE	30.000 h
INSULATION CLASS	CLASS II
IP RATING	IP20
LIGHTING DISTRIBUTION	DIRECT
COLOR TEMPERATURE	2700 / 3000 / 4000 K
CRI	80
LIGHTING FLUX	2850 / 2925 / 3075 lm
LUMINOUS EFFICACY	99 / 101,6 / 106,8 lm/W



CODE	DESCRIPTION
QBOP21X21SY2780150000	PROFILE 21X21 suspended 28,8 W 2700K Ra80 2850lm IP20 1500lm white
QBOP21X21SY3080150000	PROFILE 21X21 suspended 28,8 W 3000K Ra80 2925lm IP20 1500lm white
QBOP21X21SY4080150000	PROFILE 21X21 suspended 28,8 W 4000K Ra80 3075lm IP20 1500lm white
QBOP21X21SY2780150001	PROFILE 21X21 suspended 28,8 W 2700K Ra80 2850lm IP20 1500lm aluminum
QBOP21X21SY3080150001	PROFILE 21X21 suspended 28,8 W 3000K Ra80 2925lm IP20 1500lm aluminum
QBOP21X21SY4080150001	PROFILE 21X21 suspended 28,8 W 4000K Ra80 3075lm IP20 1500lm aluminum
QBOP21X21SY2780150009	PROFILE 21X21 suspended 28,8 W 2700K Ra80 2850lm IP20 1500lm black
QBOP21X21SY3080150009	PROFILE 21X21 suspended 28,8 W 3000K Ra80 2925lm IP20 1500lm black
QBOP21X21SY4080150009	PROFILE 21X21 suspended 28,8 W 4000K Ra80 3075lm IP20 1500lm black

