


p2+1 pro luminaire



RANGE	PROFILE 2+1 PRO LUMINAIRE
REF.	QBOP2+1PROY-
TYPE	SUSPENDED MOUNTING
DIMENSIONS	65 x 85 x 1200 mm
MATERIAL	ALUMINUM
FINISHED	WHITE / ALUMINUM / BLACK
VOLTAGE	100 - 277 V
FREQUENCY	50 / 60 Hz
FEEDER KIT	INCLUDED
DIMMABLE	NO
POWER	TRACK: 3000 W / LED STRIPS: 31,2 W
SERVICE LIFE	30.000 h
IP RATING	IP20
LIGHTING DISTRIBUTION	DIRECT
COLOR TEMPERATURE	2700 / 3000 / 4000 K
CRI	95
LIGHTING FLUX	DIRECT LED STRIP: 2635 / 2760 / 2875 lm



COLOR TEMPERATURE (K)	LIGHTING FLUX (lm)	LUMINOUS EFFICACY (lm/W)
2700	2635	84,6
3000	2760	88,5
4000	2875	92,3

CODE	DESCRIPTION
QBOP2+1PROYTD2795120000	PROFILE 2+1 PRO suspended T: 3000W L: 31,2W 2700K Ra95 2635lm IP20 1200mm white
QBOP2+1PROYTD3095120000	PROFILE 2+1 PRO suspended T: 3000W L: 31,2W 3000K Ra95 2760lm IP20 1200mm white
QBOP2+1PROYTD4095120000	PROFILE 2+1 PRO suspended T: 3000W L: 31,2W 4000K Ra95 2875lm IP20 1200mm white
QBOP2+1PROYTD2795120001	PROFILE 2+1 PRO suspended T: 3000W L: 31,2W 2700K Ra95 2635lm IP20 1200mm aluminum
QBOP2+1PROYTD3095120001	PROFILE 2+1 PRO suspended T: 3000W L: 31,2W 3000K Ra95 2760lm IP20 1200mm aluminum
QBOP2+1PROYTD4095120001	PROFILE 2+1 PRO suspended T: 3000W L: 31,2W 4000K Ra95 2875lm IP20 1200mm aluminum
QBOP2+1PROYTD2795120009	PROFILE 2+1 PRO suspended T: 3000W L: 31,2W 2700K Ra95 2635lm IP20 1200mm black
QBOP2+1PROYTD3095120009	PROFILE 2+1 PRO suspended T: 3000W L: 31,2W 3000K Ra95 2760lm IP20 1200mm black
QBOP2+1PROYTD4095120009	PROFILE 2+1 PRO suspended T: 3000W L: 31,2W 4000K Ra95 2875lm IP20 1200mm black