

## p2+1 pro luminaire



RANGE	PROFILE 2+1 PRO LUMINAIRE
REF.	QBOP2+1PROY-
TYPE	SUSPENDED MOUNTING
DIMENSIONS	65 x 85 x 2000 mm
MATERIAL	ALUMINUM
FINISHED	WHITE / ALUMINUM / BLACK
VOLTAGE	100 - 270 V
FREQUENCY	50 / 60 Hz
FEEDER KIT	INCLUDED
DIMMABLE	NO
POWER	TRACK: 3000 W / LED STRIPS: 52 W
SERVICE LIFE	30.000 h
IP RATING	IP20
LIGHTING DISTRIBUTION	DIRECT
COLOR TEMPERATURE	2700 / 3000 / 4000 K
CRI	95
LIGHTING FLUX	DIRECT LED STRIP: 4395 / 4600 / 4795 lm



COLOR TEMPERATURE (K)	LIGHTING FLUX (lm)	LUMINOUS EFFICACY (lm/W)
2700	4395	84,6
3000	4600	88,5
4000	4795	92,3

CODE	DESCRIPTION
QBOP2+1PROYTD2795200000	PROFILE 2+1 PRO suspended T: 3000W L: 52W 2700K Ra95 4395lm IP20 2000mm white
QBOP2+1PROSTD3095200000	PROFILE 2+1 PRO suspended T: 3000W L: 52W 3000K Ra95 4600lm IP20 2000mm white
QBOP2+1PROSTD4095200000	PROFILE 2+1 PRO suspended T: 3000W L: 52W 4000K Ra95 4795lm IP20 2000mm white
QBOP2+1PROYTD2795200001	PROFILE 2+1 PRO suspended T: 3000W L: 52W 2700K Ra95 4395lm IP20 2000mm aluminum
QBOP2+1PROSTD3095200001	PROFILE 2+1 PRO suspended T: 3000W L: 52W 3000K Ra95 4600lm IP20 2000mm aluminum
QBOP2+1PROSTD4095200001	PROFILE 2+1 PRO suspended T: 3000W L: 52W 4000K Ra95 4795lm IP20 2000mm aluminum
QBOP2+1PROYTD2795200009	PROFILE 2+1 PRO suspended T: 3000W L: 52W 2700K Ra95 4395lm IP20 2000mm black
QBOP2+1PROSTD3095200009	PROFILE 2+1 PRO suspended T: 3000W L: 52W 3000K Ra95 4600lm IP20 2000mm black
QBOP2+1PROSTD4095200009	PROFILE 2+1 PRO suspended T: 3000W L: 52W 4000K Ra95 4795lm IP20 2000mm black

