

profile h3 Ra80



| | |
|-----------------------|------------------------------|
| RANGE | LUMINAIRE H3 |
| REF. | QBOPH3- |
| TYPE | SURFACE OR SUSPENDED PROFILE |
| DIMENSIONS | 50 x 83 x 1500 mm |
| MATERIAL | ALUMINIUM |
| ALLOY | 6063 |
| RESISTANCE | T5 |
| ANODIZE | 20µm |
| FINISH | WHITE / ALUMINIUM / BLACK |
| VOLTAGE | 230 V |
| FEEDER KIT | INCLUDED |
| DIMMABLE | NO |
| POWER | 57,6 W |
| SERVICE LIFE | > 50.000 HRS |
| INSULATION CLASS | CLASS I |
| IP RATING | IP20 |
| LIGHTING DISTRIBUTION | DIRECT |
| COLOR TEMPERATURE | 2700K / 3000K / 4000K |
| CRI | 80 |
| MACADAM ELLIPSE | 2 |
| LIGHTING FLUX | 4648lm / 4798lm / 4947lm |

*Diferentes acabados y longitudes de perfil disponibles bajo pedido
Other finishes and profile lengths available on request

*Compatible con todas las potencias y medidas de tiras de LED qbo Flexy
Compatible with all power and measures of qbo Flexy LED strips



| CODE | DESCRIPTION |
|---------------------|--|
| QBOPH35762780150000 | PROFILE H3 57,6W 2700K Ra80 4648lm 120lpµm IP20 230V 1500mm white |
| QBOPH35763080150000 | PROFILE H3 57,6W 3000K Ra80 4798lm 120lpµm IP20 230V 1500mm white |
| QBOPH35764080150000 | PROFILE H3 57,6W 4000K Ra80 4947lm 120lpµm IP20 230V 1500mm white |
| QBOPH35762780150001 | PROFILE H3 57,6W 2700K Ra80 4648lm 120lpµm IP20 230V 1500mm aluminum |
| QBOPH35763080150001 | PROFILE H3 57,6W 3000K Ra80 4798lm 120lpµm IP20 230V 1500mm aluminum |
| QBOPH35764080150001 | PROFILE H3 57,6W 4000K Ra80 4947lm 120lpµm IP20 230V 1500mm aluminum |
| QBOPH35762780150009 | PROFILE H3 57,6W 2700K Ra80 4648lm 120lpµm IP20 230V 1500mm black |
| QBOPH35763080150009 | PROFILE H3 57,6W 3000K Ra80 4798lm 120lpµm IP20 230V 1500mm black |
| QBOPH35764080150009 | PROFILE H3 57,6W 4000K Ra80 4947lm 120lpµm IP20 230V 1500mm black |

profile h3^{acc}

| CODE | DESCRIPTION |
|-------------|--|
| QBOP04UL | PROFILE 04 9x1mm linear union (4 units) |
| QBOP04UAE | PROFILE 04 9x1mm angular union (4 units) |
| QBOPH3F | PROFILE H3 fixing clip (1 unit) |
| QBOKITSUSPY | PROFILE kit suspension Y |