

profile h3 Ra80 dali



RANGE	LUMINAIRE H3
REF.	QBOPH3-
TYPE	SURFACE OR SUSPENDED PROFILE
DIMENSIONS	50 x 83 x 3000 mm
MATERIAL	ALUMINIUM
ALLOY	6063
RESISTANCE	T5
ANODIZE	20µm
FINISH	WHITE / ALUMINIUM / BLACK
VOLTAGE	230 V
FEEDER KIT	INCLUDED
DIMMABLE	YES
POWER	76,8 W
SERVICE LIFE	> 50.000 HRS
INSULATION CLASS	CLASS I
IP RATING	IP20
LIGHTING DISTRIBUTION	DIRECT
COLOR TEMPERATURE	2700K / 3000K / 4000K
CRI	80
MACADAM ELLIPSE	2
LIGHTING FLUX	7600lm / 7800lm / 8200lm

*Diferentes acabados y longitudes de perfil disponibles bajo pedido
Other finishes and profile lengths available on request

*Compatible con todas las potencias y medidas de tiras de LED qbo Flexy
Compatible with all power and measures of qbo Flexy LED strips



CODE	DESCRIPTION
QBOPH3768278020000D	PROFILE H3 76,8W 2700K Ra80 7600lm 120µm IP20 230V 2000mm white DALI
QBOPH3768308020000D	PROFILE H3 76,8W 3000K Ra80 7800lm 120µm IP20 230V 2000mm white DALI
QBOPH3768408020000D	PROFILE H3 76,8W 4000K Ra80 8200lm 120µm IP20 230V 2000mm white DALI
QBOPH3768278020000ID	PROFILE H3 76,8W 2700K Ra80 7600lm 120µm IP20 230V 2000mm aluminum DALI
QBOPH3768308020000ID	PROFILE H3 76,8W 3000K Ra80 7800lm 120µm IP20 230V 2000mm aluminium DALI
QBOPH3768408020000ID	PROFILE H3 76,8W 4000K Ra80 8200lm 120µm IP20 230V 2000mm aluminum DALI
QBOPH37682780200009D	PROFILE H3 76,8W 2700K Ra80 7600lm 120µm IP20 230V 2000mm black DALI
QBOPH37683080200009D	PROFILE H3 76,8W 3000K Ra80 7800lm 120µm IP20 230V 2000mm black DALI
QBOPH37684080200009D	PROFILE H3 76,8W 4000K Ra80 8200lm 120µm IP20 230V 2000mm black DALI

profile h3^{acc}

CODE	DESCRIPTION
QBOP04UL	PROFILE 04 9x1mm linear union (4 units)
QBOP04UAE	PROFILE 04 9x1mm angular union (4 units)
QBOPH3F	PROFILE H3 fixing clip (1 unit)
QBOKITSUSPY	PROFILE kit suspension Y