

profile h3 Ra80 IP55



RANGE	LUMINAIRE H3
REF.	QBOPH3-
TYPE	SURFACE OR SUSPENDED PROFILE
DIMENSIONS	50 x 83 x 3000 mm
MATERIAL	ALUMINIUM
ALLOY	6063
RESISTANCE	T5
ANODIZE	20µm
FINISH	WHITE / ALUMINIUM / BLACK
VOLTAGE	230 V
FEEDER KIT	INCLUDED
DIMMABLE	NO
POWER	115,2 W
SERVICE LIFE	> 50.000 HRS
INSULATION CLASS	CLASS I
IP RATING	IP55
LIGHTING DISTRIBUTION	DIRECT
COLOR TEMPERATURE	2700K / 3000K / 4000K
CRI	80
MACADAM ELLIPSE	2
LIGHTING FLUX	11400lm / 11700lm / 12300lm

*Diferentes acabados y longitudes de perfil disponibles bajo pedido
Other finishes and profile lengths available on request

*Compatible con todas las potencias y medidas de tiras de LED qbo Flexy
Compatible with all power and measures of qbo Flexy LED strips



CODE	DESCRIPTION
QBOPH3115278055300000	PROFILE H3 115,2W 2700K Ra80 11.400lm 120lpµm IP55 230V 3000mm white
QBOPH3115308055300000	PROFILE H3 115,2W 3000K Ra80 11.700lm 120lpµm IP55 230V 3000mm white
QBOPH3115408055300000	PROFILE H3 115,2W 4000K Ra80 12.300lm 120lpµm IP55 230V 3000mm white
QBOPH3115278055300001	PROFILE H3 115,2W 2700K Ra80 11.400lm 120lpµm IP55 230V 3000mm aluminum
QBOPH3115308055300001	PROFILE H3 115,2W 3000K Ra80 11.700lm 120lpµm IP55 230V 3000mm aluminum
QBOPH3115408055300001	PROFILE H3 115,2W 4000K Ra80 12.300lm 120lpµm IP55 230V 3000mm aluminum
QBOPH3115278055300009	PROFILE H3 115,2W 2700K Ra80 11.400lm 120lpµm IP55 230V 3000mm black
QBOPH3115308055300009	PROFILE H3 115,2W 3000K Ra80 11.700lm 120lpµm IP55 230V 3000mm black
QBOPH3115408055300009	PROFILE H3 115,2W 4000K Ra80 12.300lm 120lpµm IP55 230V 3000mm black

profile h3^{acc}

CODE	DESCRIPTION
QBOP04UL	PROFILE 04 9x1mm linear union (4 units)
QBOP04UAE	PROFILE 04 9x1mm angular union (4 units)
QBOPH3F	PROFILE H3 fixing clip (1 unit)
QBOKITSUSPY	PROFILE kit suspension Y