



## profile h3<sup>acc</sup>

RANGE	PROFILE H3 SPOT
REF.	QBOPH3S-
TYPE	RECESSED
DIMENSIONS	280 x 45 x 49 mm
WEIGHT	0,5 Kg
MATERIAL	ALUMINIUM
FINISH	WHITE FRAME
VOLTAGE	200 - 240 V
FREQUENCY	50 / 60 Hz
FEEDER KIT	600 mA
DIMMABLE	YES
POWER	20 W
SERVICE LIFE	> 30.000 HRS
INSULATION CLASS	CLASS II
IP RATING	IP20
OPERATING TEMPERATURE	-20°C to +50° C
LIGHTING DISTRIBUTION	DIRECT
COLOR TEMPERATURE	3000 / 4000 K
CRI	90
LIGHTING FLUX	1273 / 1464 lm
LUMINOUS EFFICACY	63,7 / 73,2 lm/w
OPENING DEGREES	15° / 30°
WARRANTY	3 YEARS



CODE	DESCRIPTION
QBOPH3S10.20301590D	PROFILE H3 spot10 recessed 20W 3000K Ra90 15° 1273lm dali
QBOPH3S10.20401590D	PROFILE H3 spot10 recessed 20W 4000K Ra90 15° 1464lm dali
QBOPH3S10.20303090D	PROFILE H3 spot10 recessed 20W 3000K Ra90 30° 1273lm dali
QBOPH3S10.20403090D	PROFILE H3 spot10 recessed 20W 4000K Ra90 30° 1464lm dali

\*FEEDER KIT NOT PLACEABLE OVER THE DOWNLIGHT. SHOULD BE PLACED ASIDE.  
(See below recommended accessories)

## profile h3<sup>acc</sup>

CODE	DESCRIPTION
QBOPH3P	PROFILE H3 linear plate 3000mm
QBOPH3P00L	PROFILE H3 linear plate 3000mm white lacquered
QBOPH3P09L	PROFILE H3 linear plate 3000mm black lacquered