



profile h3^{acc}

RANGE	PROFILE H3 SPOT
REF.	QBOPH3S-
TYPE	RECESSED
DIMENSIONS	147 x 45 x 49 mm
WEIGHT	0,28 Kg
MATERIAL	ALUMINIUM
FINISH	WHITE FRAME
VOLTAGE	200 - 240 V
FREQUENCY	50 / 60 Hz
FEEDER KIT	700 mA
DIMMABLE	YES
POWER	10 W
SERVICE LIFE	> 30.000 HRS
INSULATION CLASS	CLASS II
IP RATING	IP20
OPERATING TEMPERATURE	-20°C to +50° C
LIGHTING DISTRIBUTION	DIRECT
COLOR TEMPERATURE	3000 / 4000 K
CRI	90
LIGHTING FLUX	494 / 568 lm
LUMINOUS EFFICACY	49,4 / 56,8 lm/w
OPENING DEGREES	15° / 30°
WARRANTY	3 YEARS



CODE	DESCRIPTION
QBOPH3S5.10301590D	PROFILE H3 spot5 recessed 10W 3000K Ra90 15° 494lm dali
QBOPH3S5.10401590D	PROFILE H3 spot5 recessed 10W 4000K Ra90 15° 568lm dali
QBOPH3S5.10303090D	PROFILE H3 spot5 recessed 10W 3000K Ra90 30° 494lm dali
QBOPH3S5.10403090D	PROFILE H3 spot5 recessed 10W 4000K Ra90 30° 568lm dali

*FEEDER KIT NOT PLACEABLE OVER THE DOWNLIGHT. SHOULD BE PLACED ASIDE.
(See below recommended accessories)

profile h3^{acc}

CODE	DESCRIPTION
QBOPH3P	PROFILE H3 linear plate 3000mm
QBOPH3P00L	PROFILE H3 linear plate 3000mm white lacquered
QBOPH3P09L	PROFILE H3 linear plate 3000mm black lacquered