

spot^{OR}



RANGE	SPOT ORIENTABLE DOWNLIGHT
REF.	QBOSPOT-
TYPE	RECESSED
DIMENSIONS	444 x 105 x 96 mm
MATERIAL	ALUMINIUM
FINISH	WHITE FRAME
CUT HOLE	425 x 90mm
VOLTAGE	200 - 240 V
FREQUENCY	50 / 60 Hz
FEEDER KIT	600 mA
DIMMABLE	YES
POWER	30 W
SERVICE LIFE	> 30.000 HRS
INSULATION CLASS	CLASS II
IP RATING	IP20
OPERATING TEMPERATURE	-20°C to +50° C
LIGHTING DISTRIBUTION	DIRECT
COLOR TEMPERATURE	3000 / 4000 K
CRI	90
LIGHTING FLUX	1420 / 1632 lm
LUMINOUS EFFICACY	47,3 / 54,4 lm/w
OPENING DEGREES	15° / 30°
WARRANTY	3 YEARS



CODE	DESCRIPTION
QBOSPOT15OR.30301590	SPOT10 DOWNLIGHT orientable 30W 3000K Ra90 15° 1420lm dali
QBOSPOT15OR.30401590	SPOT10 DOWNLIGHT orientable 30W 4000K Ra90 15° 1632lm dali
QBOSPOT15OR.30303090	SPOT10 DOWNLIGHT orientable 30W 3000K Ra90 30° 1420lm dali
QBOSPOT15OR.30403090	SPOT10 DOWNLIGHT orientable 30W 4000K Ra90 30° 1632lm dali