



spot^T

RANGE	SPOT TRIMLESS DOWNLIGHT
REF.	QBOSPOT-
TYPE	RECESSED
DIMENSIONS	91 x 69 x 49 mm
WEIGHT	0,20 Kg
MATERIAL	ALUMINIUM
FINISH	WHITE FRAME
CUT HOLE	72 x 41mm
VOLTAGE	200 - 240 V
FREQUENCY	50 / 60 Hz
FEEDER KIT	600 mA
DIMMABLE	YES
POWER	4 W
SERVICE LIFE	> 30.000 HRS
INSULATION CLASS	CLASS II
IP RATING	IP20
OPERATING TEMPERATURE	-20°C to +50° C
LIGHTING DISTRIBUTION	DIRECT
COLOR TEMPERATURE	3000 / 4000 K
CRI	90
LIGHTING FLUX	217 / 250 lm
LUMINOUS EFFICACY	54,3 / 62,5 lm/w
OPENING DEGREES	15° / 30°
WARRANTY	3 YEARS



CODE	DESCRIPTION
QBOSPOT2T.4301590D	SPOT2 DOWNLIGHT trimless 4W 3000K Ra90 15° 217lm dali
QBOSPOT2T.4401590D	SPOT2 DOWNLIGHT trimless 4W 4000K Ra90 15° 250lm dali
QBOSPOT2T.4303090D	SPOT2 DOWNLIGHT trimless 4W 3000K Ra90 30° 217lm dali
QBOSPOT2T.4403090D	SPOT2 DOWNLIGHT trimless 4W 4000K Ra90 30° 250lm dali