

brick

RANGE	BRICK
REF.	BRICK-
TYPE	LED WALL LUMINAIRE
INSTALLATION	SURFACE
DIMENSIONS	projector Ø35x55mm / profile 31x31x200mm
MATERIAL	ALUMINIUM
FINISH	WHITE / BLACK
LIGHT SOURCE	LED COB
VOLTAGE	220 - 240 V
FREQUENCY	50 / 60 Hz
FEEDER KIT	REMOTE (200mA)
DIMMABLE	YES (button)
POWER	7W
SERVICE LIFE	40.000 HRS
IP RATING	IP20
LIGHTING DISTRIBUTION	DIRECT
COLOR TEMPERATURE	2700 / 3000 K
CRI	90
LUMINAIRE FLUX	from 690lm to 715lm
OPENING DEGREES	30°
TILTING VERTICAL AXIS	90°
ROTATION HORIZONTAL AXIS	355°



CODE	DESCRIPTION
BRICK-	BRICK wall-

* Remote driver included

reference builder

TYPE	POWER	C. TEMP	BEAM ANG	CRI	FINISH	DIMMING
BRICK (wall)	7 (7W)	27 (2700K) 30 (3000K)	30°	90 (CRI>90)	00 (white) 09 (black)	D (DIM)

Order example:
BRICK 7 27 30 90 00 D
BRICK wall 7W 2700K 30° CRI90 white finish DIM

