

## dla G2 100mm

|                              |                         |
|------------------------------|-------------------------|
| RANGE                        | TRIDONIC LED MODULE AC  |
| REF.                         | TR2800224-              |
| TYPE                         | DOWNLIGHT               |
| DIMENSIONS                   | ø114 x 77 mm            |
| FREE HEIGHT FOR INSTALLATION | 100 mm                  |
| WEIGHT                       | 0,193kg                 |
| FINISH                       | BLUE AND WHITE          |
| VOLTAGE                      | 220 - 240 V             |
| FREQUENCY                    | 50 / 60 Hz              |
| FEEDER KIT                   | INCLUDED                |
| DIMMABLE                     | NO                      |
| POWER                        | 10,2 W                  |
| POWER FACTOR                 | 0,9                     |
| SERVICE LIFE                 | 50.000h (L70)           |
| IP RATING                    | IP20                    |
| OPERATING TEMPERATURE        | -20 a 40 °C             |
| LIGHTING DISTRIBUTION        | DIRECT                  |
| COLOR TEMPERATURE            | 3000 K / 4000 K         |
| CRI                          | 80                      |
| MACADAM ELLIPSE              | 4                       |
| LIGHTING FLUX                | 1060 lm / 1110 lm       |
| LUMINOUS EFFICACY            | 103,9 lm/w / 108,8 lm/w |
| OPENING DEGREES              | 60° / 90°               |



+



+



### reference builder

| TYPE               | SHAPE               | ADJUSTABLE        | POWER          | C. TEMP       | BEAM        | CRI            | FINISH         | Ø               |
|--------------------|---------------------|-------------------|----------------|---------------|-------------|----------------|----------------|-----------------|
| DLA<br>(downlight) | SQ<br>(round sq.)   | F<br>(fixed)      | 102<br>(10,2W) | 30<br>(3000K) | 60<br>(60°) | 90<br>(CRI>90) | 00L<br>(white) | .100<br>(100mm) |
|                    | RO<br>(round round) | O<br>(orientable) |                | 40<br>(4000K) | 90<br>(90°) |                |                |                 |

Other color temperatures available under request  
Depending on the chosen distance, you can only choose the power of the same horizontal.

### Order example:

DLA SQ 102 30 90 90 00L .100  
DLA downlight square 10,2W 3000K 90° CRI 90 white finish 100 mm

