

## DLA G2 150mm

RANGE	TRIDONIC LED MODULE AC
TYPE	DOWNLIGHT
DIMENSIONS	Ø164 x 107 mm
FREE HEIGHT FOR INSTALLATION	150 mm
WEIGHT	0,317kg
FINISH	BLUE AND WHITE
VOLTAGE	220 - 240 V
FREQUENCY	50 / 60 Hz
FEEDER KIT	INCLUDED
DIMMABLE	NO
POWER	10,1 W / 20,2 W
POWER FACTOR	0,9
SERVICE LIFE	50.000h (L70)
IP RATING	IP20
OPERATING TEMPERATURE	-20 a 40 °C
LIGHTING DISTRIBUTION	DIRECT
COLOR TEMPERATURE	3000 K / 4000 K
CRI	90
MACADAM ELLIPSE	4
LIGHTING FLUX	1100 lm / 2170 lm
LUMINOUS EFFICACY	108,9 lm/w / 107,4 lm/w
OPENING DEGREES	60° / 90°



### reference builder

TYPE	SHAPE	ADJUSTABLE	POWER	C. TEMP	BEAM	CRI	FINISH	Ø
DLA150 (downlight)	SQ (round sq.)	F (fixed)	101 (10,1W)	30 (3000K)	60 (60°)	90 (CRI>90)	00L (white)	150 (150mm)
	RO (round round)	O (orientable)	202 (20,2W)	40 (4000K)	90 (90°)			

Other color temperatures available under request  
Depending on the chosen distance, you can only choose the power of the same horizontal.

### Order example:

DLA SQ 202 30 90 90 00L 150  
DLA downlight square 20,2W 3000K 90° CRI 90 white finish 150 mm