

## flexy ECO IP



RANGE	QBO FLEXY ECO
REF.	05075-
TYPE	LEDSTRIP
DIMENSIONS	13 x 5000 mm
CUT UNIT	125 mm
MINIMUM BENDING DIAMETRE	50 mm
MAXIMUM RUN LENGTH	10000 mm
MAXIMUM CABLE LENGTH (FOR MAX RUN LENGTH)	(ø 0,5 mm) 5000 mm
GAP BETWEEN LEDS	16 mm
WEIGHT	0,275 Kg
VOLTAGE	24 V
DIMMABLE	YES
POWER	7,56 W
SERVICE LIFE	> 50000 HRS
IP RATING	IP67
LIGHTING DISTRIBUTION	DIRECT / INDIRECT
CRI	80
MACADAM ELLIPSE	5
LPM	48 lpm
OPENING DEGREES	120 °
WARRANTY	3 YEARS

\*DOES NOT NEED DISSIPATION

COLOR TEMPERATURE (K)	LIGHTING FLUX (lm)	LUMINOUS EFFICACY (lm/W)
2200	550	72,7
2700	560	74,1
3000	570	75,4
4000	610	80,7
6500	600	79,4



CODE	DESCRIPTION
050752258067	LEDSTRIP FLEXY Eco 7,56W/m 2200K 5m Ra80 550lm/m 48leds/m IP67 24V
050752758067	LEDSTRIP FLEXY Eco 7,56W/m 2700K 5m Ra80 560lm/m 48leds/m IP67 24V
050753058067	LEDSTRIP FLEXY Eco 7,56W/m 3000K 5m Ra80 570lm/m 48leds/m IP67 24V
050754058067	LEDSTRIP FLEXY Eco 7,56W/m 4000K 5m Ra80 610lm/m 48leds/m IP67 24V
050756558067	LEDSTRIP FLEXY Eco 7,56W/m 6500K 5m Ra80 600lm/m 48leds/m IP67 24V

