

flexy^{HE}

RANGE	QBO FLEXY HE
REF.	01192-
TYPE	LEDSTRIP
DIMENSIONS	12 x 5000 mm
CUT UNIT	50 mm
MINIMUM BENDING DIAMETRE	50 mm
MAXIMUM RUN LENGTH	5000 mm
GAP BETWEEN LEDS	6,25 mm
WEIGHT	0,150 Kg
VOLTAGE	DC 24 V
DIMMABLE	YES
POWER	18 W
SERVICE LIFE	> 50.000 HRS
IP RATING	IP20
LIGHTING DISTRIBUTION	DIRECT / INDIRECT
CRI	90
MACADAM ELLIPSE	3
LPM	160 lpm
OPENING DEGREES	140 °
WARRANTY	5 YEARS

*NEEDS DISSIPATION

*OTHER COLOR TEMPERATURES AND CRI AVAILABLE UNDER REQUEST



COLOR TEMPERATURE (K)	LIGHTING FLUX (lm)	LUMINOUS EFFICACY (lm/W)
2700	2574	143
3000	2646	147
4000	2850	158,3



REACH



CODE	DESCRIPTION
0218027590	LEDSTRIP FLEXY HE 18W/m 2700K 5m Ra90 2574lm/m 160leds/m IP20 24V
0218030590	LEDSTRIP FLEXY HE 18W/m 3000K 5m Ra90 2646lm/m 160leds/m IP20 24V
0218040590	LEDSTRIP FLEXY HE 18W/m 4000K 5m Ra90 2850lm/m 160leds/m IP20 24V

