


flexy HO



RANGE	QBO FLEXY HO
REF.	01192-
TYPE	LEDSTRIP
DIMENSIONS	10 x 5000 mm
CUT UNIT	50 mm
MINIMUM BENDING DIAMETRE	50 mm
MAXIMUM RUN LENGTH	5000 mm
MAXIMUM CABLE LENGTH (FOR MAX RUN LENGTH)	($\phi=0,5$ mm) 1500 mm
GAP BETWEEN LEDS	5 mm
WEIGHT	0,130 Kg
VOLTAGE	24 V
DIMMABLE	YES
POWER	19,2 W
SERVICE LIFE	> 50.000 HRS
IP RATING	IP20
LIGHTING DISTRIBUTION	DIRECT / INDIRECT
CRI	90
MACADAM ELLIPSE	2
LPM	120 lpm
OPENING DEGREES	140 °
WARRANTY	5 YEARS

*NEEDS DISSIPATION

COLOR TEMPERATURE (K)	LIGHTING FLUX (lm)	LUMINOUS EFFICACY (lm/W)
2200	1460	76
2700	1700	88,5
3000	1740	90,6
4000	1780	92,7
6500	1750	91,1



CODE	DESCRIPTION
0119222590	LEDSTRIP FLEXY HO 19,2W/m 2200K 5m Ra90 1460lm/m 120leds/m IP20 24V
0119227590	LEDSTRIP FLEXY HO 19,2W/m 2700K 5m Ra90 1700lm/m 120leds/m IP20 24V
0119230590	LEDSTRIP FLEXY HO 19,2W/m 3000K 5m Ra90 1740lm/m 120leds/m IP20 24V
0119240590	LEDSTRIP FLEXY HO 19,2W/m 4000K 5m Ra90 1780lm/m 120leds/m IP20 24V
0119265590	LEDSTRIP FLEXY HO 19,2W/m 6500K 5m Ra90 1750lm/m 120leds/m IP20 24V

