Data sheet www.qboiluminacion.com

Luxha HexOne

by Rafael Urquiza


RANGE	HexOne
REF.	HEXONE-
TYPE	Suspended luminaire
DIMENSIONS (custom-made possibility)	840 x 840 x 1680 mm
MATERIAL	ALUMINIUM
FINISH	WHITE / BLACK / ALUMINIUM / COPPER
INSTALLATION	SURFACE
FEEDER KIT	INCLUDED
DIMMABLE	YES
POWER	18W
SERVICE LIFE	50.000 HOURS
WARRANTY	5 years
IP RATING	IP20
OPERATING TEMPERATURE	-25°C to +55°C
LIGHTING DISTRIBUTION	DIRECT
COLOR TEMPERATURE	2700K / 3000K / 4000K / 6500K
CRI	90
LIGHTING FLUX	2574-2850 lm
LUMINOUS EFFICACY	143-158,3 lm/w
OPENING DEGREES	140°













reference builder

TYPE	PROFILE	POWER	INSTALL	C. TEMP	CRI	FINISH	DIMING	POLYGON SIDE	LIGHTING
	31 (31x31mm)		S (surface)	27 (2700K)	80 (CRI>80)	01 (anodized aluminium) 00L (white)	- (on/off)	. 840 (840mm)	IN (interior)
HEXONE (profile)		18 (18 W/m)		30 (3000K)		09L (black)			UP (up)
	2+1* (80x30mm)		Y (suspended)		90 (CRI>90)	02L (pale gold)	D (dali)	.xxx (custom)	EX (Exterior)
				40 (4000K)		22L (copper)			DN
						01L (silver)			(Down)

^{*2+1} profiles includes indirect light (14,4W)
Other color temperatures, IP rathing and finishes available under request
Driver included (2+1 includes the driver inside),
Different distance available under request.

Order example:
HEXONE 31 18 Y 40 90 01L D .200
HexCombi with 31 profile 18W suspended 4000K CRi90 silver finish DALI 200 mm hexagon side