

lite surface

RANGE	LITE
REF.	LITES-
TYPE	LED SURFACE LUMINAIRE
CEILING INSTALLATION	SURFACE
DIMENSIONS	Ø40 x 440 mm
MATERIAL	ALUMINIUM
FINISH	WHITE / BRASS SATIN / BLACK / BLUED BRASS
LIGHT SOURCE	LED MODULE
VOLTAGE	220 - 240 V
FREQUENCY	50 / 60 Hz
FEEDER KIT	INTEGRATED / REMOTE (180mA)
DIMMABLE	TRIAC
POWER	6W
SERVICE LIFE	40.000 HRS
IP RATING	IP40
LIGHTING DISTRIBUTION	DIRECT
COLOR TEMPERATURE	2700 / 3000 / 4000 K
CRI	90
LIGHTING FLUX	from 345lm to 517lm
OPENING DEGREES	18° / 30° / 50°




CODE	DESCRIPTION
LITES-	LITE surface-

* Remote driver for 190mm
 ** Integrated driver for 400mm

reference builder

TYPE	LENGTH	POWER	C. TEMP	BEAM ANG	CRI	FINISH	DIMMING	
LITES (surface)	M (190mm)	6 (6W)	27 (2700K)	18°	90 (CRI>90)	00 (white)	T (TRIAC)	
	L (440mm)		30 (3000K)	30°		02 (brass satin)		
			40 (4000K)	50°		09 (black)		
						13 (blued brass)		



Order example:
 LITES M 6 27 50 90 13 T
 LITE spotlight surface M 190mm 6W
 2700K 50° CRI90 blued brass finish TRIAC

