

lite wall

RANGE	LITE
REF.	LITEW-
TYPE	LED SURFACE LUMINAIRE
INSTALLATION	SURFACE
DIMENSIONS	Ø40 x 190 mm
MATERIAL	ALUMINIUM
FINISH	BRASS SATIN / BLUED BRASS
LIGHT SOURCE	LED MODULE
VOLTAGE	220 - 240 V
FREQUENCY	50 / 60 Hz
FEEDER KIT	REMOTE (180mA)
DIMMABLE	TRIAC
POWER	6W
SERVICE LIFE	40.000 HRS
IP RATING	IP40
LIGHTING DISTRIBUTION	DIRECT
COLOR TEMPERATURE	2700 / 3000 / 4000 K
CRI	90
LIGHTING FLUX	from 345lm to 517lm
OPENING DEGREES	18° / 30° / 50°
TILTING VERTICAL AXIS	355°
ROTATION HORIZONTAL AXIS	355°



CODE	DESCRIPTION
LITEW-	LITE wall-

* Remote driver included

reference builder

TYPE	POWER	C. TEMP	BEAM ANG	CRI	FINISH	DIMMING
LITEW (wall)	6 (6W)	27 (2700K)	18°	90 (CRI>90)	02 (brass satin)	T (TRIAC)
		30 (3000K)	30°		13 (blued brass)	
		40 (4000K)	50°			

Order example:
LITEW 6 27 18 90 13 T
LITE spotlight wall 6W
2700K 18° CRI90 blued brass finish TRIAC

