

2+1 wall

RANGE	2+1 PROFILE LUMINAIRE
REF.	2+1W-
TYPE	LED WALL SURFACE LUMINAIRE
SECTION	Ø30 x 80 mm
MATERIAL	ALUMINIUM
FINISH	WHITE / BLACK / BRONZE
VOLTAGE	220 - 240 V
FREQUENCY	50 / 60 Hz
FEEDER KIT	INCLUDED
INSULATION CLASS	CLASS II (indoor) / CLASS III (outdoor)
POWER (one side emission)	14,4W/m
POWER (two sides emission)	28,8W/m
SERVICE LIFE	50.000 HRS
IP RATING	IP55
LIGHTING DISTRIBUTION	DIRECT + INDIRECT
COLOR TEMPERATURE	2700 / 3000 / 4000 K
CRI	90
MACADAM ELLIPSE	3
DIRECT LIGHTING FLUX	1600 lm/m
INDIRECT LIGHTING FLUX	1600 lm/m
LUMINOUS EFFICIENCY	111 lm/m



CODE	DESCRIPTION
2+1W-	2+1 WALL luminaire-

* Integrated driver for indoor use

* Remote driver for outdoor use

reference builder

TYPE	EMISSION	C. TEMP	CRI	FINISH	DIMMING	LENGTH
2+1W (wall lamp)	U (light up)	27 (2700K)	90 (CRI>90)	00 (white)	- (on/off)	.51 (510mm)
	D (light down)	30 (3000K)		09 (black)		.76 (760mm)
	UD (light up & down)	40 (4000K)		19 (bronze)	D (DALI)	.101 (1010mm)

Order example:

2+1W UD 40 90 19 - .76

2+1 WALL LAMP light up & down

4000K CRI90 bronze finish on/off 760mm

