

TimyLed Small

RANGE	QBO TIMYLED
REF.	QBOTIMYS-
TYPE	RAIL LED PROJECTOR
DIMENSIONS	H130 x Ø86,5 mm
MATERIAL	ALUMINUM
FINISH	BLACK RAL 9005
VOLTAGE	220 - 240 V
FREQUENCY	50 / 60 Hz
FEEDER KIT	800 mA
DIMMABLE	YES
POWER	29 W
POWER FACTOR	0,9
SERVICE LIFE	> 35.000 HRS
WARRANTY	5 YEARS
INSULATION CLASS	CLASS II
IP RATING	IP20
LIGHTING DISTRIBUTION	DIRECT
COLOR TEMPERATURE	2700 / 3000 / 4000 K
CRI	80
MACADAM ELLIPSE	3
LIGHTING FLUX	4031 / 4188 / 4329 lm
LUMINOUS EFFICACY	139 / 144 / 149 lm/w
OPENING DEGREES	12° / 24° / 36°
TILTING VERTICAL AXIS	90°
ROTATION HORIZONTAL AXIS	350°



CODE	DESCRIPTION
------	-------------

TIMYS- TIMY LED SMALL projector

* DRIVER INCLUDED

reference builder

TYPE	INSTALL	POWER	C. TEMP	BEAM	CRI	FINISH	DIMING
TIMYS (projector)	- (track)	29 (29W)	27 (2700K)	12 (12°)	80 (CRI>80)	00 (white)	-
	T (trim)		30 (3000K)	24 (24°)		01 (silver)	
	R (rosette)		40 (4000K)	36 (36°)	90 (CRI>90)	02 (brass)	D (DALI)
						09 (black)	

Order example:

TIMYS - 29 30 12 90 00 D

TIMY SMALL projector track 29W 3000K 12° CRI90 white finish DALI

